

---

# Release Notes for X11R7.6

The X.Org Foundation [<http://www.x.org/wiki/XorgFoundation>]

December 2010

## Abstract

These release notes contain information about features and their status in the X.Org Foundation X11R7.6 release.

## Table of Contents

Dedication .....	1
Introduction to the X11R7.6 Release .....	1
Summary of new features in X11R7.6 .....	2
Overview of X11R7.6 .....	3
Details of X11R7.6 components .....	4
Video Drivers .....	4
Input Drivers .....	6
Xorg server .....	6
Font support .....	9
Build changes and issues .....	10
Silent build rules .....	10
New configure options for font modules .....	10
New configure options for documentation in modules .....	10
Miscellaneous .....	10
Socket directory ownership and permissions .....	11
Deprecated components and removal plans .....	11
Future Removals .....	11
Removed in this Release .....	12
Attributions/Acknowledgements/Credits .....	12

## Dedication

*Two of the early leaders of the X Window System community were lost to cancer this year — Smokey Wallace, who led the DEC WSL team which created the initial implementation of X11, and Hideki Hiura from Sun Microsystems who helped design the X11R6 internationalization framework. This release is dedicated to their memory.*

## Introduction to the X11R7.6 Release

This release is the seventh modular release of the X Window System™. The next full release will be X11R7.7 and is expected in 2011.

Unlike X11R1 through X11R6.9, X11R7.x releases are not built from one monolithic source tree, but many individual modules. These modules are distributed as individual source code releases, and each one is released when it is ready, instead of only when the overall window system is ready for release. The X11R7.x releases are made by “rolling up” the individual module releases into a collection that is often affectionately called the “katamari” by the developers.

The X11R7.6 release does not include all of the software formerly included in the previous X Window System releases. It is designed to be a reasonable baseline from which to start when building the window system for the first time for a new installation, distribution, or package set. It does not provide a full desktop environment, expecting a more feature rich set of applications to be installed from one of the several excellent desktop environments available for the X Window System. The X.Org developers continue to maintain and produce new releases of much of the software that was formerly in the main window system releases but is no longer included in the katamari releases, including many of the Athena Widgets desktop applications that were provided as samples in previous window system versions.

Once their window system build is established, most builders watch for announcements of individual module updates on the [xorg-announce mailing list](http://lists.freedesktop.org/mailman/listinfo/xorg-announce) [http://lists.freedesktop.org/mailman/listinfo/xorg-announce] and update to those as needed. The X.Org Foundation currently releases the X Window System katamari releases approximately once a year, but many modules, especially the X servers and drivers, are updated more frequently between those releases.

For help with how to build and develop in the modular tree see the [Modular Developer's Guide](http://wiki.x.org/wiki/ModularDevelopersGuide) [http://wiki.x.org/wiki/ModularDevelopersGuide] in the X.Org wiki.

We encourage you to report bugs using freedesktop.org's [bug tracking system](https://bugs.freedesktop.org/) [https://bugs.freedesktop.org/] using the xorg product, and to submit bug fixes and enhancements to <xorg-devel@lists.x.org>. More details on patch submission and review process are available on the [SubmittingPatches](http://www.x.org/wiki/Development/Documentation/SubmittingPatches) [http://www.x.org/wiki/Development/Documentation/SubmittingPatches] page of the X.Org wiki.

The release numbering is based on the original MIT X numbering system. X11 refers to the version of the network protocol that the X Window system is based on: Version 11 was first released in 1988 and has been stable for 22 years, with only upward compatible additions to the core X protocol, a record of stability envied in computing. Formal releases of X started with X version 9 from MIT; the first commercial X products were based on X version 10. The MIT X Consortium and its successors, the X Consortium, the Open Group X Project Team, and the X.Org Group released versions X11R3 through X11R6.6. Since the founding of the X.Org Foundation in early 2004, many further releases have been issued, from X11R6.7 to the current 7.6.

The next section describes what is new in the latest full release (7.6) compared with the previous full release (7.5).

## Summary of new features in X11R7.6

This is a sampling of the new features in X11R7.6. A more complete list of changes can be found in the ChangeLog files that are part of the source of each X module.

- *InputClass* sections in Xorg configuration files are used to apply configuration options to any input device matching specified rules, such as device path, type of device, device manufacturer, or other data provided by the input hotplug backend. Details can be found in the `INPUTCLASS` section of the [xorg.conf\(5\)](http://xorg.conf.5.html) [xorg.conf.5.html] manual page.
- *Xorg configuration directories* are used to allow fragments of the X server configuration to be delivered in individual files. For instance, the input device driver

matching rules previously provided in HAL `.fdi` files are now provided as `InputClass` sections in `.conf` files in a `xorg.conf.d` directory.

- *udev* is now used by the X server on Linux systems for input device discovery and hot-plug notification. Other platforms continue to use the HAL framework for these tasks for now.
- *X protocol C-language Binding (XCB)* is now included in the `katamari`, and is required by several client-side modules, including `libX11`, **`xlsatoms`**, **`xlsclients`** and **`xwininfo`**. XCB is a replacement for Xlib featuring a small footprint, latency hiding, direct access to the protocol, improved threading support, and extensibility. More information can be found on the XCB website at <http://xcb.freedesktop.org/>.
- Major progress has been made on the X.Org Documentation modernization - most of the library and protocol specifications are now included in the modules for those libraries and protocols so they can be updated in sync with new versions, and many have been converted to DocBook XML from the variety of formats they were previously in. On most systems these documents will be installed under `/usr/share/doc/`. They are also posted on the X.Org website at <http://www.x.org/releases/X11R7.6/>.
- *Video and input driver enhancements*. Please see the ChangeLog files for individual drivers; there are far too many updates to list here.
- ... and the usual assortment of correctness and crash fixes.

## Overview of X11R7.6

On most platforms, X11R7.6 has a single hardware-driving X server binary called **Xorg**. This binary can dynamically load the video drivers, input drivers, and other modules that are needed. **Xorg** has currently has support for Linux, Solaris, and some BSD OSs on Alpha, PowerPC, IA-64, AMD64, Intel x86, Sparc, and MIPS platforms.

Additional specialized X server binaries may be found depending on the platform and build configuration, including:

**Xdmx** is a proxy X server that uses one or more other X servers as its display devices. It provides multi-head X functionality for displays that might be located on different machines.

**Xnest** is a nested X server, that operates as both an X client and X server. **Xnest** is a client of the real server which manages windows and graphics requests on its behalf. **Xnest** is a server to its own clients, and manages windows and graphics requests on their behalf. To these clients, it appears to be a conventional server.

**Xephyr** is a X server that outputs to a window on a pre-existing "host" X display. Unlike **Xnest** which is an X proxy, and thus limited to the capabilities of the host X server, **Xephyr** is a full X server which uses the host X server window as a "framebuffer" via fast SHM XImages.

<b>Xvfb</b>	is a virtual framebuffer X server that can run on machines with no display hardware and no physical input devices. It emulates a dumb framebuffer using virtual memory.
<b>Xquartz</b>	is an X server that interacts with the MacOS X native Aqua window system, displaying windows on the Mac desktop and accepting input from the Mac system devices, allowing X11 applications to be used in a native Mac desktop session.
<b>Xwin</b>	is an X server that runs under the Cygwin environment, interacting with the Microsoft Windows native window system, displaying windows on the Windows desktop and accepting input from the Windows system devices, allowing X11 applications to be used in a native Windows desktop session.

## Details of X11R7.6 components

### Video Drivers

X11R7.6 includes the following video drivers:

Driver Name	Description	Further Information
apm	Alliance Pro Motion	<a href="#">README.apm</a> [apm.html]
ark	Ark Logic	
ast	ASPEED Technology	
chips	Chips & Technologies	<a href="#">README.chips</a> [chips.html], <a href="#">chips(4)</a> [chips.4.html]
cirrus	Cirrus Logic	
fbdev	Linux framebuffer device	<a href="#">fbdev(4)</a> [fbdev.4.html]
geode (*)	AMD Geode GX and LX	
glint	3Dlabs, TI	<a href="#">glint(4)</a> [glint.4.html]
i128	Number Nine	<a href="#">README.I128</a> [I128.html], <a href="#">i128(4)</a> [i128.4.html]
i740	Intel i740	<a href="#">README.i740</a> [i740.html]
imstt	Integrated Micro Solns	
intel	Intel i8xx/i9xx	<a href="#">README.intel</a> [intel.html], <a href="#">intel(4)</a> [intel.4.html]
mach64	ATI Mach64	<a href="#">README.ati</a> [ati.html]
mga	Matrox	<a href="#">mga(4)</a> [mga.4.html]
neomagic	NeoMagic	<a href="#">neomagic(4)</a> [neomagic.4.html]

newport (-)	SGI Newport	<a href="#">README.newport</a> [newport.html], <a href="#">newport(4)</a> [newport.4.html]
nsc	National Semiconductor	<a href="#">nsc(4)</a> [nsc.4.html]
nv	NVIDIA	<a href="#">nv(4)</a> [nv.4.html]
r128	ATI Rage128	<a href="#">README.r128</a> [r128.html], <a href="#">r128(4)</a> [r128.4.html]
radeon	ATI Radeon	<a href="#">radeon(4)</a> [radeon.4.html]
rendition	Rendition	<a href="#">README.rendition</a> [rendition.html], <a href="#">rendition(4)</a> [rendition.4.html]
s3	S3 (not ViRGE or Savage)	
s3virge	S3 ViRGE	<a href="#">README.s3virge</a> [s3virge.html], <a href="#">s3virge(4)</a> [s3virge.4.html]
savage	S3 Savage	<a href="#">savage(4)</a> [savage.4.html]
siliconmotion	Silicon Motion	<a href="#">siliconmotion(4)</a> [siliconmotion.4.html]
sis	SiS	<a href="#">README.SiS</a> [SiS.html], <a href="#">sis(4)</a> [sis.4.html]
sisusb	SiS USB	<a href="#">sisusb(4)</a> [sisusb.4.html]
suncg14 (+)	Sun cg14	
suncg3 (+)	Sun cg3	
suncg6 (+)	Sun GX and Turbo GX	
sunffb (+)	Sun Creator/3D, Elite 3D	
sunleo (+)	Sun Leo (ZX)	
suntcx (+)	Sun TCX	
tdfx	3Dfx Voodoo Banshee, 3, 4 & 5	<a href="#">tdfx(4)</a> [tdfx.4.html]
tga	DEC TGA	<a href="#">README.DECtga</a> [DECtga.html]
trident	Trident	<a href="#">trident(4)</a> [trident.4.html]
tseng	Tseng Labs	
v4l	Video4Linux	<a href="#">v4l(4)</a> [v4l.4.html]
vesa	VESA	<a href="#">vesa(4)</a> [vesa.4.html]
vmware	VMware guest OS	<a href="#">vmware(4)</a> [vmware.4.html]
voodoo	3Dfx Voodoo 1 & 2	<a href="#">voodoo(4)</a> [voodoo.4.html]
wsfb	Workstation Framebuffer	<a href="#">wsfb(4)</a> [wsfb.4.html]
xgi	XGI	<a href="#">xgi(4)</a> [xgi.4.html]
xgixp	XGI XP	<a href="#">xgixp(4)</a> [xgixp.4.html]

Drivers marked with (\*) are present in a preliminary form in this release, but are not complete and/or stable yet.

Drivers marked with (+) are for Linux/Sparc only.

Drivers marked with (-) are for Linux/mips only.

## Input Drivers

X11R7.6 includes the following input drivers:

Driver Name	Description	Further Information
acecad	Acecad Flair	<a href="#">acecad(4)</a> [aiptek.4.html]
aiptek (*)	Aiptek USB tablet	<a href="#">aiptek(4)</a> [aiptek.4.html]
evdev (*)	Linux kernel EvDev	<a href="#">evdev(4)</a> [evdev.4.html]
joystick	Joystick	<a href="#">joystick(4)</a> [joystick.4.html]
kbd	generic keyboards (non-evdev systems)	<a href="#">kbd(4)</a> [kbd.4.html]
mouse	most mouse devices (non-evdev systems)	<a href="#">mousedrv(4)</a> [mousedrv.4.html]
synaptics	Synaptics & ALP touch-pads	<a href="#">synaptics(4)</a> [synaptics.4.html]
vmmouse	VMWare virtual mouse	<a href="#">vmmouse(4)</a> [vmmouse.4.html]
void	dummy device	<a href="#">void(4)</a> [void.4.html]

Drivers marked with (\*) are available for Linux only.

## Xorg server

### Loader and Modules

The Xorg server relies on the operating system's native module loader support for handling program modules. The X server makes use of modules for video drivers, X server extensions, input device drivers, framebuffer layers, and internal components used by some drivers (like XAA & EXA).

The module interfaces (both API and ABI) used in this release are subject to change without notice. While we will attempt to provide backward compatibility for the module interfaces, we cannot guarantee this. Compatibility in the other direction is explicitly not guaranteed because new modules may rely on interfaces added in new releases.

### Note about module security

The X server runs with root privileges, i.e., the X server loadable modules also run with these privileges. For this reason we recommend that all users be careful to only use loadable modules from reliable sources, otherwise the

introduction of viruses and contaminated code can occur and wreak havoc on your system. We hope to have a mechanism for signing/verifying the modules that we provide available in a future release.

## Configuration File

The Xorg server uses a configuration file as the primary mechanism for providing configuration and run-time parameters. The configuration file format is described in detail in the [xorg.conf\(5\)](#) [xorg.conf.5.html] manual page.

Note that this release features significant improvements for running the server without a configuration file, so many users may find that they don't need a configuration file.

If you do need to customize the configuration file, see the [xorg.conf manual page](#) [xorg.conf.5.html] . You can also check the driver-specific manual pages and the related documentation (found at [driver tables](#)) also.

The recommended method for generating a configuration file is to use the Xorg server itself. Run as root:

```
Xorg -configure
```

and follow the instructions.

## Command Line Options

Command line options can be used to override some default parameters and parameters provided in the configuration file. These command line options are described in the [Xorg\(1\)](#) [Xorg.1.html] manual page.

## Multi-head

Some multi-head configurations are supported in X11R7.6. Support for multiple PCI/AGP cards may require a kernel with changes to support VGA arbitration.

One of the main problems is with drivers not sufficiently initializing cards that were not initialized at boot time. This has been improved somewhat with the INT10 support that is used by most drivers (which allows secondary card to be "soft-booted", but in some cases there are other issues that still need to be resolved. Some combinations can be made to work better by changing which card is the primary card (either by using a different PCI slot, or by changing the system BIOS's preference for the primary card).

## Xinerama

*Xinerama* is an X server extension that allows multiple physical screens connected to multiple video devices to behave as a single screen. With traditional multi-head in X11, windows cannot span or cross physical screens. Xinerama removes this limitation. Xinerama does, however, require that the physical screens all have the same root depth, so it isn't possible, for example, to use an 8-bit screen together with a 16-bit screen in Xinerama mode.

Xinerama is not enabled by default, and can be enabled with the `+xinerama` command line option for the X server. Note that enabling Xinerama may disable certain other extensions which are not compatible with Xinerama.

## DDC

The VESA® Display Data Channel (DDC™) standard allows the monitor to tell the video card (or in some cases the computer directly) about itself; particularly the supported screen resolutions and refresh rates.

Partial or complete DDC support is available in most of the video drivers. DDC is enabled by default, but can be disabled with a "Device" section entry: `Option "NoDDC"`. We have support for DDC versions 1 and 2; these can be disabled independently with `Option "NoDDC1"` and `Option "NoDDC2"`.

At startup the server prints out DDC information from the display, and can use this information to set the default monitor parameters, or to warn about monitor sync limits if those provided in the configuration file don't match those that are detected.

### Changed behavior caused by DDC.

Several drivers use DDC information to set the screen size and pitch. This can be overridden by explicitly resetting it to the and non-DDC default value 75 with the `-dpi 75` command line option for the X server, or by specifying appropriate screen dimensions with the "DisplaySize" keyword in the "Monitor" section of the config file.

## GLX and the Direct Rendering Infrastructure (DRI)

Direct rendered OpenGL® support is provided for several hardware platforms by the Direct Rendering Infrastructure (DRI). Further information about DRI can be found at the [DRI Project's web site](http://dri.sf.net/) [http://dri.sf.net/]. The 3D core rendering component is provided by [Mesa](http://www.mesa3d.org) [http://www.mesa3d.org].

Of note is that this release supports building the X server using the system-wide `libdrm`. Previously, `drm` was kept in the server's tree and loaded as a module, rather than using the standard OS mechanisms for managing shared libraries of code. This requires that the server be built using a version of `libdrm` of 2.3.0 or newer if it is to use DRM.

## Terminate Server keystroke

The Xorg server has previously allowed users to exit the server by pressing the keys **Control + Alt + Backspace**. While this function is still enabled by default in this release, the keymap data usually used with Xorg, from the `xkeyboard-config` project, has been modified to not map that sequence by default, in order to reduce the chance that inexperienced users will accidentally destroy their work.

Users who wish to have this functionality available by default may enable it via the XKB configuration option `"terminate:ctrl_alt_bksp"`. For instance, the **setxkbmap** command can be used to enable this by running:

```
setxkbmap -option "terminate:ctrl_alt_bksp"
```



The [XKB Configuration Guide](#) [input/XKB-Config.html] also includes [an example xorg.conf.d file that sets the “terminate:ctrl\\_alt\\_bksp” option by default on all keyboards](#) [input/XKB-Config.html#zap]. Many desktop environments include XKB configuration options in their preferences to enable this as well.

## X Server startup state

The X servers in the X11R7.6 release now start by default with an empty black screen and do not draw the mouse cursor until a client sets the cursor image. To restore the classic behavior of starting with the grey weave pattern and × cursor, start the X server with the `-retro` option.

## Font support

Details about the font support in X11R7.6 can be found in the “[Fonts in X11R7.6](#) [fonts/fonts.html]” document.

## Default font installation directory

Previous versions of X installed font files under the `lib/X11/fonts` subdirectory of the X installation directory (for instance, in X11R6 releases, `/usr/X11R6/lib/X11/fonts` was commonly used). This release uses the default installation path of the `fonts` subdirectory of the `datadir` setting from the GNU autoconf configuration. For instance, if the fonts are configured with `./configure --prefix=/usr`, they will be installed under subdirectories of `/usr/share/fonts/X11`. The font module configure scripts all take an option of `--with-fontrootdir=PATH` to override the default. If `--with-fontrootdir` is not specified, the `fontutil pkg-config` file will be consulted to find the `fontrootdir` specified when the `fontutil` module was installed.

## Bitmap font compression methods

The X11R7.6 release supports PCF format bitmap fonts stored uncompressed or compressed via the **compress**, **gzip**, or **bzip2** programs. To utilize `bzip2` compression, the `libXfont` and **mkfontscale** modules must be built with the `--with-bzip2` — all other methods are enabled by default.

To specify which compression method to use when installing a font module from X11R7.6 the configure scripts accept an option of `--with-compression=TYPE`, where `TYPE` may be `none`, `compress`, `gzip`, or `bzip2`.

## Type1 Font support

Previous versions of X came with two Postscript Type1 font backends. The functionality from the “Type1” backend has been replaced by the Type1 support in the “FreeType” backend.

## CID Font support

The CID-keyed font format was designed by Adobe Systems for fonts with large character sets. The CID-keyed format is obsolete, as it has been superseded by other formats such as OpenType/CFF and support for CID-keyed fonts has been removed from X11.

## Build changes and issues

### Silent build rules

Most of the modules in this release use the `AM_SILENT_RULES` option of GNU automake 1.11. When building the software, most output will show an abbreviated format for the commands being run, such as:

```
CC xmen.o
```

To enable verbose output, showing all the arguments to the commands being run, add the flag `v=1` to the **make** command line or add the flag `--disable-silent-rules` to the configure command.

### New configure options for font modules

The bitmap font modules now accept a configure option of `--disable-all-encodings` to set the default for all encodings to off, requiring builders to then pass `--enable-<encoding>` flags for each encoding to be built.

### New configure options for documentation in modules

As many more modules now contain documentation to be converted from DocBook XML to text, HTML, PostScript, and/or PDF formats, new standard options have been added to the configure macros to control the build of these in the modules.

<code>--with-xmlto=yes/no</code>	Enables or disables use of the <a href="https://fedorahosted.org/xmlto/">xmlto</a> [https://fedorahosted.org/xmlto/] command to translate DocBook XML to other formats. All DocBook XML conversions require use of this command.
<code>--with-fop=yes/no</code>	Enables or disables use of the <a href="http://xmlgraphics.apache.org/fop/">Apache fop</a> [http://xmlgraphics.apache.org/fop/] command to translate DocBook XML to PostScript and PDF formats.
<code>--enable-docs=yes/no</code>	Enables or disables the build and installation of all documentation except traditional man pages or those covered by the <code>--enable-devel-docs</code> and <code>--enable-specs</code> options.
<code>--enable-devel-docs=yes/no</code>	Enables or disables the build and installation of documentation for developers of the X.Org software modules.
<code>--enable-specs=yes/no</code>	Enables or disables the build and installation of the formal specification documents for protocols and APIs.

## Miscellaneous

This section describes other items of note for the X11R7.6 release.

## Socket directory ownership and permissions

The socket directories created in `/tmp` are now required to be owned by root and have their sticky-bit set. If the permissions are not set correctly, the component using this directory will print an error message and fail to start. Common socket directories that are known to be affected include:

```
/tmp/.font-unix
/tmp/.ICE-unix
/tmp/.X11-unix
```

These directories are used by the font server (**xfs**), applications using the Inter-Client Exchange protocol (ICE) and the X server, respectively.

There are several solutions to the problem of when to create these directories. They could be created at install time by the system's installer if the `/tmp` dir is persistent. They could be created at boot time by the system's boot scripts (e.g., the `init.d` scripts). Or, they could be created by PAM modules at service startup or user login time.

The solution chosen is platform dependent, and the system administrator should be able to handle creating those directories on any systems that do not have the correct ownership or permissions.

## Deprecated components and removal plans

This section lists current plans for removal of obsolete or deprecated components in the X.Org releases. As our releases are open source, users who continue to require these can find the source in previous releases and continue to use these, but the X.Org Foundation and its volunteers have decided the burden of continued maintenance and distribution in the core X11 releases outweighs the benefits of doing so. In some cases, this is simply because no one has volunteered to do continued maintenance, so if software is listed here that you need, you can contact [xorg@lists.freedesktop.org](mailto:xorg@lists.freedesktop.org) to volunteer to take over maintainership, either inside or outside of the Xorg release process.

### Future Removals

DGA version 2

DGA 2.0 is included in 7.6. Documentation for the client libraries can be found in the [XDGA\(3\)](#) [`XDGA.3.man`] man page. DGA should be considered deprecated; if you are relying on it, please let us know what you need it for so we can find better solutions. In this release, support has been removed for all DGA rendering and mapping code, leaving just mode setting and raw input device access.

Input device discovery via HAL

The Xorg server currently uses the [HAL framework](#) [<http://www.freedesktop.org/wiki/Software/hal>] to discover connected input devices, receive notification of hotplug events for them, and to retrieve con-

figuration parameters for them. The HAL maintainers have deprecated HAL, so the X.Org developers have begun replacement with alternatives. As a result, configuration of input devices via HAL \*.fdi files is no longer supported on Linux platforms using udev, and may not be supported on other platforms in future Xorg server releases.

## Removed in this Release

Xprint	The Xprint server and extension were previously removed from X11R7.5. This release removes Xprint support from a number of client programs that still had it.
Xsdl server	The experimental Xsdl server has never been finished or maintained, and was removed in this release.
Unmaintained extensions	Support has been removed from the X servers for the following extensions, which were obsolete, not widely used, or not working: <ul style="list-style-type: none"><li>• Multi-Buffering</li></ul>

## Attributions/Acknowledgements/Credits

This section lists the credits for the X11R7.6 release. For a more detailed breakdown, refer to the ChangeLog file in the source tree for each module, the history in [the xorg product in freedesktop.org's git repositories](http://cgit.freedesktop.org/xorg/product) [<http://cgit.freedesktop.org/xorg/>] or the 'git log' information for individual source files.

The X Window System has been a collaborative effort from its inception. Our apologies for anyone or organization inadvertently overlooked. Many individuals (including major contributors) who worked on X are represented by their employers in this list. If you feel we have left anyone out, please let us know.

These people contributed in some way to X11R7.6 since the release of X11R7.5:

邓逸昕	Kim Woelders
Aaron Plattner	Kok, Auke
Aaron Zang	Kristian Høgsberg
Adam Jackson	Kusanagi Kouichi
Adam Tkac	Lee Leahu
Adrian 'Dagurashibanipal' von Bidder	Leif Middelschulte
Adrian Bunk	Leonardo Chiquitto
Alan Coopersmith	Lubos Lunak
Alberto Milone	Luc Verhaegen
Alex Deucher	Luca Tettamanti
Alex Warg	Ma Ling
Alexander Kabaev	Maarten Maathuis
Alp Toker	Macpaul Lin
Andrej Gelenberg	Magnus Kessler
Andres Salomon	Marc Majka
Andrew Chant	Marcin Baczyński

Andrew Randrianasulu	Marcin Kościelnicki
Andrzej Hajda	Marcin Slusarz
Andy Furniss	Marek Olšák
Andy Ritger	Mario Kleiner
Antoine Latter	Mark Kettenis
Arkadiusz Miśkiewicz	Marko Myllynen
Arnaud Fontaine	Markus Duft
Auke Kok	Markus Gapp
Bart Massey	Markus Strobl
Bartek Iwaniec	Mart Raudsepp
Bartosz Brachaczek	Martin Ettl
Ben Byer	Martin Otte
Ben Hutchings	Martin Pärtel
Ben Skeggs	Martin-Éric Racine
Benjamin Close	Márton Németh
Benjamin Tissoires	Matt Dew
Bernhard R. Link	Matt Turner
Bob Ham	Matteo Delfino
Brian Paul	Matthias Hopf
Brice Goglin	Matthieu Herrb
Bryce Harrington	Matthijs Kooijman
Carl Worth	Michael Cree
Carlos Garnacho	Michael Jansen
Carsten Meier	Michael Olbrich
Cedric Cellier	Michael Ost
Chase Douglas	Michael Stapelberg
Chris Bagwell	Michael Vogt
Chris Ball	Michał Górny
Chris Dekter	Michel Dänzer
Chris Humbert	Mikhail Gusarov
Chris Wilson	Nicolai Hähnle
Christian Bühler	Nicolas Boullis
Christian Hartmann	Nicolas George
Christian Zander	Nicolas Reinecke
Christoph Pfister	Nigel Tamplin
Christopher James Halse Rogers	Nirbheek Chauhan
Cody Maloney	Oldřich Jedlička
Colin Harrison	Oliver McFadden
Colin Watson	Olivier Samyn
Cooper Yuan	Osamu Sayama
Corbin Simpson	Oswald Buddenhagen
Csillag Kristof	Otavio Salvador
Cyril Brulebois	Owain G. Ainsworth
Dan Nicholson	Owen W. Taylor
Daniel Drake	Patrick Caulfield
Daniel Kahn Gillmor	Patrick Curran
Daniel Stone	Patrick E. Kane
Dave Airlie	Patrick Guimond
David Ge	Paul Bender
David James	Paul Loewenstein
David Ronis	Paul "TBBle" Hampson
David Woodhouse	Pauli Nieminen
Diego 'Flameeyes' Pettenò	Paulo César Pereira de Andrade
Dima Kogan	Paulo Ricardo Zanoni

Dirk Wallenstein  
Dmitry Torokhov  
Dominik Jasiok  
Donnie Berkholz  
Eamon Walsh  
Ed Schouten  
Edward Moy  
Edward O'Callaghan  
Egbert Eich  
Eric Anholt  
Éric Piel  
Eric Sesterhenn  
Fabio Pedretti  
Fernando Carrijo  
Francisco Jerez  
Frank Huang  
Fredrik Höglund  
Gabor Z. Papp  
Gaetan Nadon  
Geoffrey Li  
Guillem Jover  
Hans Nieser  
Heikki Lindholm  
Henning Sten  
Henry Zhao  
Hiroyuki Ikezoe  
Horst Wente  
Hunk Cui  
Ian Osgood  
Ian Romanick  
Ingmar Vanhassel  
Jakob Bornecrantz  
James Cloos  
James Jones  
James Le Cuirot  
Jamey Sharp  
Jan Hauffa  
Jens Petersen  
Jeremy Huddleston  
Jeremy Kolb  
Jeroen Hoek  
Jerome Glisse  
Jesse Adkins  
Jesse Barnes  
Jim Ingram  
Jim Ramsay  
Joachim Breitner  
Jon TURNEY  
Josh Triplett  
Julien Cristau  
Julien Danjou  
Juliusz Chroboczek  
Justin Mattock  
Kalle Olavi Niemitalo

Peter Harris  
Peter Hutterer  
Peter Korsgaard  
Petr Salinger  
Philippe Ribet  
Pierre-Loup A. Griffais  
Rami Ylimäki  
Rémi Cardona  
Rémi Denis-Courmont  
Richard Barnette  
Richard Purdie  
Rob Taylor  
Robert Bragg  
Robert Hooker  
Robert Morell  
Roel Kluin  
Roland Scheidegger  
Ruediger Oertel  
Ryan Hajdaj  
Sam Lau  
Sami Farin  
Samuel Thibault  
Sascha Hlusiak  
Sedat Dilek  
Shunichi Fuji  
Simon Farnsworth  
Simon Thum  
Søren Sandmann Pedersen  
Thien-Thi Nguyen  
Thomas Coppi  
Thomas Hellstrom  
Thomas Hunger  
Thomas Jaeger  
Tiago Vignatti  
Tilman Sauerbeck  
Tim Yamin  
Timo Aaltonen  
Timo Myyra  
Tobias Droste  
Tobias Koch  
Tollef Fog Heen  
Tomas Carnecky  
Tomáš Chvátal  
Tormod Volden  
Trevor Woerner  
Ville Syrjälä  
Vincent Torri  
Walter Harms  
Will Thompson  
Wolfram  
Xavier Chantry  
Xiaoyang Yu (Max)  
Y.C. Chen  
Yaakov Selkowitz

Karl Tomlinson  
Kees Cook  
Keith Packard  
Kenneth Graunke  
Kevin E Martin  
Kevin Van Vechten

Yang Zhao  
Yann Droneaud  
Yannick Heneault  
Zephaniah E. Hull  
Zhao Yakui

This product includes software developed by:

2d3d Inc.	Kevin E. Martin
3Dlabs Inc. Ltd.	Kim woelders
Aaron Plattner	Kristian Høgsberg
Adam de Boor	Larry Wall
Adam Jackson	Lars Knoll
Adobe Systems Inc.	Lawrence Berkeley Laboratory
Advanced Micro Devices, Inc.	Leif Delgass
After X-TT Project	Lennart Augustsson
AGE Logic Inc.	Leon Shiman
Alan Coopersmith	Lexmark International Inc.
Alan Cox	Linus Torvalds
Alan Hourihane	Linuxcare Inc.
Alexander Gottwald	Lorens Younes
Alex Deucher	Luc Verhaegen
Alex Williamson	Machine Vision Holdings Inc.
Alexei Gilchrist	Mandriva Linux
Anders Carlsson	Manfred Brands
Andreas Luik	Manish Singh
Andreas Monitzer	Marc Aurele La France
Andreas Robinson	Mark Adler
Andrei Barbu	Mark J. Kilgard
Andrew C Aitchison	Mark Kettenis
Andrey A. Chernov	Mark Leisher
Andy Ritger	Mark Smulders
Angus Lees	Mark Vojkovich
Ani Joshi	Martin Husemann
Anton Zioviev	Marvin Solomon
Apollo Computer Inc.	Massachusetts Inst. Of Technology
Apple Computer Inc.	Matrox Graphics
Apple Inc.	Matt Dew
Ares Software Corp.	Matthew Grossman
Arnaud LE HORS	Matthias Hopf
Arne Schwabe	Matthias Ihmig
ASPEED Technology Inc.	Matthieu Herrb
AT&T Inc.	Metro Link Inc.
ATI Technologies Inc.	Michal Rehacek
Bart Massey	Michael Bax
Bart Trojanowski, Symbio Technologies, LLC	Michael H. Schimek
BEAM Ltd.	Michael P. Marking
Benjamin Herrenschmidt	Michael Schimek
Benjamin Riefenstahl	Michael Smith
Ben Skeggs	Michel Dänzer
Beth Mardutho: The Syriac Institute	Mike A. Harris
Bigelow and Holmes	Mike Harris

Bill Reynolds	Ming Yu
Bitstream Inc.	MIPS Computer Systems Inc.
Bogdan Diaconescu	MontaVista Software Inc.
Branden Robinson	National Security Agency
Brian Fundakowski Feldman	National Semiconductor
Brian Goines	NCR Corporation Inc.
Bogdan D.	Neil Brown
Brian Paul	NetBSD Foundation
Bruce Kalk	Netscape Communications Corp.
Bruno Haible	Network Computing Devices Inc.
Bryan Stine	New Mexico State University
Bryan W. Headley.	Nicholas Joly
C. Scott Ananian	Nicholas Miell
Carl Switzky	Nicholas Wourms
Catharon Productions Inc.	Nicolai Haehnle
Charles Murcko	Noah Levitt
Chen Xiangyang	Nolan Leake
Chisato Yamauchi	Nokia Corporation
Chris Constello	Nokia Home Communications
Chris Salch	Novell Inc.
Christian Thaeter	Nozomi YTOW
Christian Zietz	NTT Software Corporation
Cognition Corp.	Number Nine Computer Corp.
Compaq Computer Corporation	Number Nine Visual Technologies
Concurrent Computer Corporation	NVIDIA Corporation
Conectiva S.A.	Oivier Danet
Corin Anderson	Oki Technosystems Laboratory Inc.
Corvin Zahn.	Olivetti Research Limited
Cronyx Ltd.	OMRON Corporation
Craig Struble	Open Software Foundation
Daewoo Electronics Co. Ltd.	Open Text Corporation
Dag-Erling Smørgrav	OpenedHand Ltd.
Dale Schumacher	Oracle Corp.
Damien Miller	Orest Zborowski
Daniel Berrange	Owen Taylor
Daniel Borca	Pablo Saratxaga
Daniel Stone	Panacea Inc.
Daniver Limited	Panagiotis Tsirigotis
Daryll Strauss	Paolo Severini
Data General Corporation	Pascal Haible
Dave Airlie	Patrick Lecoanet
David Bateman	Patrick Lerda
David Dawes	Paul Anderson
David E. Wexelblat	Paul Elliott
David Holland	Paul Mackerras
David J. McKay	Peter Breitenlohner
David McCullough	Peter Hutterer
David Mosberger-Tang	Peter Kunzmann
David Reveman	Peter Osterlund
David S. Miller	Peter Trattler
David Woodhouse	Phil Karlton
Davor Matic	Philip Blundell
Deron Johnson	Philip Homburg
Digeo Inc.	Philip Langdale



Dennis De Winter	Precision Insight Inc.
Digital Equipment Corporation	Prentice Hall
Dirk Hohndel	Quarterdeck Office Systems
Dmitry Golubev	Radek Doulik
Donnie Berkholz	Ralf Habacker
DOS-EMU-Development-Team	Randy Hendry
Doug Anson	Ranier Keller
Drew Parsons	Red Hat Inc.
Earle F. Philhower III	Regis Cridlig
Edouard TISSERANT	Rene Cougnenc
Eduard Fuchs	Richard A. Hecker
Eduardo Horvath	Richard Burdick
Egbert Eich	Rich Murphey
Egmont Koblinger	Rickard E. Faith
Elliot Lee	Rik Faith
Eric Anholt	Robert Chesler
Eric Fortune	Robert Millan
Eric Sunshine	Robert V. Baron
Erik Fortune	Robert W. Scheifler
Erik Nygren	Robin Cutshaw
Evans & Sutherland Computer Corp.	Roland Mainz
Fabio Massimo Di Nitto	Roland Scheidegger
Fabrizio Gennari	Ronny Vindenes
Fedor P. Goncharov	Russ Blaine
Felix Kühling	Ryan Breen
Finn Thoegersen	Ryan Lortie
Francesco Zappa Nardelli	Ryan Underwood
Frank C. Earl	S. Lehner
Florian Loitsch	S3 Graphics Inc.
Francisco Jerez	Sam Leffler
Fred Hucht	Santa Cruz Operation Inc.
Frederic Lepied	Sascha Hlusiak.
Fredrik Höglund	SciTech Software
Free Software Foundation	Scott Laird
Fujitsu Limited	Sebastien Marineau
Fujitsu Open Systems Solutions Inc.	Serge Winitzki
Fuji Xerox Co. Ltd.	Sergey Vovk
Gaetan Nadon	Shigehiro Nomura
Gareth Hughes	ShoGraphics Inc.
Geert Uytterhoeven	Shunsuke Akiyama
George Fufutos	Silicon Graphics Computer Systems
George Sapountzis	Silicon Graphics, Inc.
Gerrit Jan Akkerman	Silicon Integrated Systems Corp
Gerry Toll	Silicon Motion Inc.
Ghozlane Toumi	Simon P. Cooper
Glenn G. Lai	Simon Thum
GNOME Foundation	Snitily Graphics Consulting Services
Go Watanabe	Sony Corporation
Google Summer of Code participants	Søren Sandmann
Greg Kroah-Hartman	SRI
Gregory Mokhin	Stanislav Brabec
Greg Parker	Stefan Bethge
GROUPE BULL	Stefan Dirsch
Guillem Jover	Stefan Gmeiner

Guy Martin	Stephane Marchesin
Hans Oey	Stephan Lang
Harald Koenig	Steven Lang
Harm Hanemaayer	Stuart Kreitman
Harold L Hunt II	Sun Microsystems Inc.
Harry Langenbacher	SunSoft Inc.
Hartwig Felger	SuSE Inc
Henry A. Worth	Sven Luther
Henry Davies	Takis Psarogiannakopoulos
Hewlett-Packard Company	Takuma Murakami
Hideki Hiura	Takuya SHIOZAKI
Hitachi Ltd.	T. A. Phelps
Holger Veit	Tektronix Inc.
Hong Bo Peng	Theo de Raadt
Howard Greenwell	Theodore Ts'o
Hummingbird Communications Ltd.	The Open Group
Ian Romanick	The Unichrome Project
IBM Corporation	The Weather Channel Inc.
Inst. of Software Academia Sinica	Thomas E. Dickey
Intel Corporation	Thomas G. Lane
INTERACTIVE Systems Corporation	Thomas Hellström
Itai Nahshon	Thomas Mueller
Itronix Inc.	Thomas Roell
Ivan Kokshaysky	Thomas Thanner
Ivan Pascal	Thomas Winischhofer
Jakub Jelinek	Thomas Wolfram
James Tsillas	Thorsten.Ohl
Jamey Sharp	Tiago Gons
Jason Bacon	Tilman Sauerbeck
Jaymz Julian	Todd C. Miller
Jean-loup Gailly	Tomohiro KUBOTA
Jeff Hartmann	Torrey Lyons
Jeff Kirk	Torrey T. Lyons
Jeffrey Hsu	TOSHIBA Corp.
Jehan Bing	Toshimitsu Tanaka
Jeremy C. Reed	Travis Tilley
Jeremy Katz	Trolltech AS
Jeremy Huddleston	Troy D. Hanson
Jerome Glisse	Tungsten Graphics Inc.
Jesse Barnes	Tuomas J. Lukka
Jim Gettys	Ty Sarna
Jim Tsillas	UCHIYAMA Yasushi
Joerg Sonnenberger	Unicode Inc.
John Dennis	UniSoft Group Limited
John Harper	University of California
John Heasley	University of South Australia
Jonathan Adamczewski	University of Utah
Jon Block	University of Wisconsin
Jon Smirl	UNIX System Laboratories Inc.
Jon Tombs	URW++ GmbH
Jörg Bösner	Valery Inozemtsev
Jorge Delgado	VA Linux Systems
José Fonseca	VIA Technologies Inc.
Josh Triplett	Video Electronics Standard Assoc.

Joseph Friedman  
Joseph P. Skudlarek  
Joseph V. Moss  
Julio M. Merino Vidal  
Juan Romero Pardines  
Juliusz Chroboczek  
Jyunji Takagi  
Kaleb Keithley  
Kazushi (Jam) Marukawa  
Kazuyuki (ikko-) Okamoto  
Kazutaka YOKOTA  
Kean Johnston  
Keith Packard  
Keith Whitwell  
Kensuke Matsuzaki

VMware Inc.  
Vrije Universiteit  
Wittawat Yamwong  
Wyse Technology Inc.  
X Consortium  
XFree86 Project Inc.  
Xi Graphics Inc.  
X-Oz Technologies  
X-TrueType Server Project  
X.Org Foundation  
XGI Technology  
Yu Shao  
Zack Rusin  
Zephaniah E. Hull  
Zhenyu Wang

This product includes software developed by The XFree86 Project, Inc (<http://www.xfree86.org/>) and its contributors.

This product includes software that is based in part on the work of the FreeType Team (<http://www.freetype.org/>).

This product includes software developed by the University of California, Berkeley and its contributors.

This product includes software developed by Christopher G. Demetriou.

This product includes software developed by the NetBSD Foundation, Inc. (<http://www.netbsd.org/>) and its contributors.

This product includes software developed by X-Oz Technologies (<http://www.x-oz.com/>).